I4KLLI60

Cable ladder interlocking ends







Side walls: perforated S-profile
Perforated C rungs 15 x 30

Usable inner height: 44 mm
Rung distance: 250 mm
To order: Length 6000 mm
To order: Width 700 - 1200 mm (increments of 100 mm)

Reference	↕ mm	↔ mm	→‖← mm	⇄ mm	kg/m	⬡	Unit
I4KLLI60.150	60	150	1	3000	2,110	30	M
I4KLLI60.200	60	200	1	3000	2,210	30	M
I4KLLI60.300	60	300	1	3000	2,400	30	M
I4KLLI60.400	60	400	1	3000	2,590	30	M
I4KLLI60.500	60	500	1	3000	2,790	30	M
I4KLLI60.600	60	600	1	3000	3,810	30	M

BELASTUNGSDIAGRAMM
This diagram illustrates the permissible uniformly distributed horizontal loads applied to multiple supports. They comply with IEC 61537 with connection in the centre of the span and the end span = 0,8x the span.

F = max. admissible load (daN/m)
L = support distance (m)
Max. deflection (m) = L/100

CHARACTERISTICS
- lightweight
- strong
- interlocking
- partition (I6SLOS35) can be fixed to the cable ladder with a sliding nut (I6GM6) and pan head bolt (I6RB6.10)
- no further coupling holes are required if the cable ladder is cut
- use joiners (I6KLLKP60) and bolts (I6VM6.10) to join the cut lenghts of cable ladder
- no joiners are required to attach accessories such as bends, tees etc.
- rungs are perforated to enable efficient attachment of cables.

TECHNICAL INFORMATION
Side walls are constructed from S profile with a return flange and are continuously perforated
Side walls are continuously perforated
C-profile rungs are fixed at 250 mm intervals
Rungs are mechanically attached to the side wall of the cable ladder
Rungs are alternately placed with openings upwards and downwards.

Pickled and passivated.

Fix with:



Toothed round head bolt / flange nut
I6VM